

High rate discharge test machine (PLT)



Your benefits:

- + Automatic high rate discharge testing of automotive batteries
- + Safe contact using tongs
- + Various test devices available
- + Exclusion station for reject batteries
- + Various expansion stages up to fully automated available
- + Automatic polarity switch available
- + Use of acid-resistant materials

High rate discharge test machine (PLT)

Technical details:

Battery type	all vehicles
Max. dimensions (W x D x H)	2,500 x 2,000 x 2,100 mm
Capacity	8 batteries/min.
Conveyor belt height	850 mm +/- 50 mm
Conveyor belt width	300 mm
Max. discharge current (PLT)	up to 3,000 A
Voltage range (PLT)	7 – 14 V
Electrical connection	400 V, 50 Hz
Control voltage	24 V
Compressed air	6 bar
Material	stainless steel, acid-resistant plastic
Control	Siemens / Allen Bradley

We offer comprehensive services and know how:



**Machines
for the production of**

Starter batteries
Traction batteries
Industrial batteries



**Advice +
Analysis**

On-site in your company



**Technical service +
Customer service**

Remote maintenance
Worldwide

Everything from a single source:

Thanks to our integration into the **Pütz Group** and the resulting **synergy effects** we are able to offer you not only battery production machines but also the appropriate testing technology to test surfaces, for dimensional accuracy and completeness.

Accumation GmbH
Lindenstraße 3
65555 Limburg-Offheim
GERMANY

info@accumation.de
Phone: +49 6431 285650-0
www.accumation.de