

# 14 BATTERY AIR BLAST DEVICE



## Function and characteristics

Remaining water is blown out automatically out of the degassing well. The batteries are delivered to the work center by means of a conveyor belt and positioned and fixed in place by an adjustable guide- and stop system. Outlet nozzles are lowered. The degassing wells are blown free with compressed air. Intensity and duration are adjustable.

## Technical data

<b>Capacity</b>	8 batteries/min
<b>Battery length</b>	175 to 400 mm
<b>Battery width</b>	125 to 200 mm
<b>Battery height</b>	165 to 283 mm
<b>Battery weight</b>	12 to 25 kg
<b>Dimensions total (L x W x H)</b>	2,000 x 1,100 x 2,400 mm
<b>Weight</b>	550 kg
<b>Material</b>	completely acid-resistant stainless steel 1.4571, 1.4539; plastics PP und PVC, special protection of all non-acid-resistant components
<b>Control voltage</b>	24 V DC
<b>Consumption</b>	2 kW
<b>Compressed air</b>	6 bar
<b>Control</b>	Siemens / Allen Bradley

## Our goods and services = Your benefit

- ▶ Worldwide technical and customer service
- ▶ Long experience in battery plant design
- ▶ Individual system solutions for your production
- ▶ Comprehensive advice and on-site analysis

### Accumation GmbH

Lindenstraße 3  
65555 Limburg-Offheim  
GERMANY

Phone: +49 6431 285650-0  
Fax: +49 6431 285650-29  
info@accumation.de  
www.accumation.de

### Good reasons for ACCUMATION ...

... we take your production on  
the road to success because  
we have the technology you  
need.

**We look forward  
to hearing from you!**