

Antistatic spray machine



Your benefits:

- + Automatic spraying of batteries with anti-static fluid
- + Low consumption using sensor-controlled spray nozzles
- + Even all-round anti-static coating of battery surfaces
- + Encasing of spray space
- + No re-tooling needed if a battery is changed
- + Use of acid-resistant materials

Antistatic spray machine

Technical details:

Battery type	all vehicles
Battery dimensions (W x D x H)	max. 515 mm x 285 mm x 250 mm min. 320 mm x 170 mm x 175 mm
Capacity	10 – 12 batteries/min.
Max. dimensions (W x D x H)	2,000 x 1,200 x 2,000 mm
Conveyor belt height	850 mm +/- 50 mm
Conveyor belt width	300 mm
Electrical connection	400 V, 50 Hz
Control voltage	24 V
Compressed air	6 bar
Material	stainless steel, acid-resistant plastic
Control	Siemens / Allen Bradley

We offer comprehensive services and know how:



**Machines
for the production of**

Starter batteries
Traction batteries
Industrial batteries



**Advice +
Analysis**

On-site in your company



**Technical service +
Customer service**

Remote maintenance
Worldwide

Everything from a single source:

Thanks to our integration into the **Pütz Group** and the resulting **synergy effects** we are able to offer you not only battery production machines but also the appropriate testing technology to test surfaces, for dimensional accuracy and completeness.

Accumation GmbH
Lindenstraße 3
65555 Limburg-Offheim
GERMANY

info@accumation.de
Phone: +49 6431 285650-0
www.accumation.de