

Gel filling machine



Your benefits:

- + Filling of AGM- or gel batteries
- + Vacuum supported filling process
- + Use of 100 % acid resistant materials
- + Volume is controlled by flowmeters or volumetric dispensing pumps
- + Accuracy +/- 0,5 % or less
- + Available for all automotive and industrial batteries

Gel filling machine

Technical details:

Battery type	all automotive batteries, also industrial types
Capacity	up to 8 batteries/min.
Change-over time	less then 5 minutes
Dimensions (W x D x H)	approx. 2,750 x 1,500 x 2,200 mm
Conveyor belt hight	850 mm
Conveyor belt width	300 mm
Material	stainless steel, acid-resistant plastic
Control voltage	24 V DC
Power consumption	approx. 3 kW
Compressed air	6 bar
Visualization	Touch Panel
Control	Siemens / Allen Bradley

We offer comprehensive services and know how:



**Machines
for the production of**

Starter batteries
Traction batteries
Industrial batteries



**Advice +
Analysis**

On-site in your company



**Technical service +
Customer service**

Remote maintenance
Worldwide

Everything from a single source:

Thanks to our integration into the **Pütz Group** and the resulting **synergy effects** we are able to offer you not only battery production machines but also the appropriate testing technology to test surfaces, for dimensional accuracy and completeness.

Accumation GmbH
Lindenstraße 3
65555 Limburg-Offheim
GERMANY

info@accumation.de
Phone: +49 6431 285650-0
www.accumation.de